SUMMARY

- The force between the atoms of an element is called inter-atomic force whereas the force between the molecules of a compound is called inter-molecular force.
- *Hooke's law:* within the elastic limit, the stress is directly proportional to strain.
- The force per unit area is known as *stress*. If F is the force applied and A is the area of cross section of the body then the magnitude of *stress* is equal to F/A. Tensile or compressional stress can be expressed using a single term called *longitudinal stress*.
- The ratio of change in length to the original length of a cylinder is $\Delta L/L$, which is known as *longitudinal strain*
- Within the elastic limit, the ratio of longitudinal stress to the longitudinal strain is called the Young' s modulus of the material of the wire.
- Within the elastic limit, the ratio of volume stress to the volume strain is called the *bulk modulus*.
- Within the elastic limit, the ratio of shear stress to the shear strain is called the *rigidity modulus*.
- Poisson's ratio = lateral strain/longitudinal strain
- The elastic potential energy stored in the wire per unit volume is $U = \frac{1}{2} \times \text{stress} \times \text{strain} = \frac{1}{2} \times Y \times (\text{strain})^2$, where Y denotes Young's modulus of the material.
- If F is the magnitude of the normal force acting on the surface area A, then the pressure is defined as the '*force acting per unit area*'.
- The total pressure at a depth h below the liquid surface is $P = P_a + \rho gh$, where P_a is the atmospheric pressure which is equal to 1.013×10^5 Pa.
- Pascal's law states that the pressure in a fluid at rest is the same at all points if they are at the same height.
- The law of floatation states that a body will float in a liquid if the weight of the liquid displaced by the immersed part of the body is equal to or greater than the weight of the body.
- The coefficient of viscosity of a liquid is the viscous force acting tangentially per unit area of a liquid layer having a unit velocity gradient in a direction perpendicular to the direction of flow of the liquid.
- When a liquid flows such that each particle of the liquid passing a point moves along the same path and has the same velocity as its predecessor then the flow of liquid is said to be streamlined flow.
- During the flow of fluid, when the critical velocity is exceeded by the moving fluid, the motion becomes *turbulent*.
- Reynold's number has a significance as it decides which decides whether the flow of fluid through a cylindrical pipe is streamlined or turbulent.

UNIT-7(XI-Physics_Vol-2)_14-08-2020.indd 87 17-08-2020 11:31:27