8. Terminal bolts are to be tightened with spring washers and apply torque. The tightness is to be checked.

Don'ts

1. Do not add any acid or distilled water in battery, during supply.
2. Do not tamper the vent plug.
3. Do not over tight or make loose the terminal bolts which may cause terminal breakage or fire due to loose contact.
4. Do not keep any metal object to rest on battery. It may cause short circuit.
5. Do not keep the battery in direct sunlight, dust or moist area.
6. Do not allow discharged battery for more than 12 hours in idle condition.

Precautions

1. Always handle a battery and its parts after wearing hand gloves, as the acid is corrosive.
2. Always pour the acid into water and not the water into the acid. Heat is produced when the acid is mixed with water.
3. Since the electrolyte is highly corrosive, the storage of electrolyte is used only glass or lead lined container If the batteries are handled with the above precautionary measures, the life of the battery will be prolonged. Follow the correct procedures and be safe while handling the battery.

4.10 NINE TIPS FOR PROPER BATTERY CARE

1. Size your battery correctly.
2. Periodically check the voltage of your batteries.
3. Don't try to charge alkaline batteries.
4. Prevent alkaline batteries from leaking.
5. Take care with parallel connections.
6. Give VRLA (Valve-Regulated Lead-Acid) battering breathing space.
7. Don't leave Lead-Acid batteries in a discharged state.
8. Take off golden ornaments when connecting a battery.
9. Protect from cold temperatures and snowy climates.

Activities

1. Test the supply voltage from lemon?
2. Test the voltage produced in carrot?
3. How to produce electricity from orange?

EMA_English_Chp04.indd 66 11/9/2020 3:01:05 PM