6.3.7 Difference Between Stone Masonry and Brick Masonry

S.No	Stone Masonry	Brick Masonry
1	The stones obtained naturally are dressed to a particular shape and used for masonry work.	The bricks are burnt in kiln and used for masonry work.
2	Stone masonry is very strong.	Strength of brick masonry is lesser than stone masonry.
3	Water tight stone masonry may be constructed.	Water tight masonry work is not possible.
4	Stone masonry does not have the property of water absorption. So this masonry is suitable for bathroom and toilets than brick masonry.	Brick walls are having the property of water absorption. To protect the walls from the dampness cement plastering is necessary.
5	Stone masonry is hard and construction is tough.	Construction of brick masonry work is easy.
6	Bonding property is not much high in stone masonry and consumption of cement mortar is also high.	Good bonding can be made in brick work. Less quantity of cement or lime mortar is used.
7	Lifting and handling of stones are not easy. So speed of masonry work is slow.	As the size of brick is small, handling and lifting is easy. So masonry work is faster.
8	In hilly areas stones are highly available. So construction cost is low.	Other than hilly area cost of brick work is economical.
9	We cannot directly use the stone which are taken from stone quarry. It should be dressed to some extent. So cost becomes high.	We can use the bricks directly from the kiln. So cost becomes low.
10	Minimum width of stone masonry should be 30 cm. Construction of stone masonry below this width is not possible.	We can construct brick walls from 10 cm thickness.
11	Heat absorption property is high for stone masonry.	Heat absorption property is not much high.

Civil_English_Unit_6.indd 151 12/21/2019 4:40:03 PM