iv. Stone
v. Tiles
vi. Terrazzo
vii. Asphalt
viii. Rubber
ix. Glass
x. Linoleum

8.3.5 Selection of Material For Flooring

Following factors are to be carefully considered before selecting the material for flooring:

1. **Appearance:** The flooring material should have desired appearance and it should produce the colour effect in conformity with the use of building.
2. **Comfort:** The flooring material should give comfort when used. Flooring material should have good thermal insulation, imparts comfort to the residents of the building to a great extent.
3. **Cost:** The cost of flooring materials should be reasonable when compared to the utility of the building.
4. **Cleaning :** The flooring materials should be such that it can be easily and effectively cleaned.
5. **Durability:** The flooring material should be durable and it should be strong enough to impart resistance to wear, tear, chemical action. etc.,
6. **Noise:** Flooring should insulate noise (i.e) it should not produce noise when users walk on it. Floor covering of wood, rubber, cork, PVC tiles are suitable for this type.
7. **Slipperiness:** Flooring material should be smooth and should have an even surface. It should not be slippery.
8. **Fire Resistant:** This quality is more important for upper floors. The material should offer sufficient fire resistance. So that fire barriers are obtained between different levels of a building. Concrete tiles, terrazo and marble have this quality

8.3.6 Types of Flooring

Following are the various types of flooring based on the materials used.

1. Tiled flooring
2. Granite flooring
3. Marble flooring
4. Precast concrete flooring
5. Plastic and PVC tile flooring
6. Carpet flooring
7. Rubber flooring

8.3.6.1 Tiled Flooring

Tiles of either clay or cement concrete or terrazzo manufactured in various shapes, size and thickness are used in this type of flooring. This flooring can be laid in shorter time.



8.3.6.2 Granite Flooring

Granite flooring is similar to granolithic flooring. Here, instead of chips, hard granite stones are laid on the sub grade of concrete. The usual thickness is 20mm to 35 mm.

Civil_English_Unit_8.indd 194 12/21/2019 5:25:21 PM