Model Question Paper II

Basic Civil Engineering– Theory

Total Marks: 90

Part A

Choose the correct answer. ***15 × 1 = 15***

1. The ebony edge of drawing board should be projected _____ from the edge of drawing board.
   a) 6 to 10 mm b) 5 to 6 mm c) 2 to 3 mm d) 7 to 8 mm
2. The software used for design of highways is _____.
   a) M.S. ROADS b) KANAL ++ c) AQUA ++ d) GEO
3. The specific gravity of good stones should be more than _____.
   a) 1.8 b) 2.1 c) 2.5 d) 2.7
4. The clay content in brick earth should be _____.
   a) 20 to 30 % b) 20 to 35 % c) 35 to 50 % d) 40 to 45 %
5. In block test, the cement block is immersed in water for _____.
   a) 5 days b) 3 days c) 7 days d) 10 days
6. _____ is the small groove cut on the underside of cornice, coping and sill to drain the rain water.
   a) Layer b) Throating c) Plinth d) Through Stone
7. The wedge shaped stones to form arch are called as _____.
   a) Voussoirs b) Extrados c) Springing stone d) Springing line
8. The horizontal member which splits window frame into two parts is _____.
   a) Transome b) Sash c) Louver d) Mullion
9. The minimum height of door is _____.
   a) 2.0 m b) 1.5 m c) 1.8 m d) 2.2 m
10. The horizontal portion of the step where we rest the foot is _____.
    a) Rise b) Tread c) Riser d) Going
11. The roof having sloped surface is known as _____.
    a) Shell roof b) Pitched roof c) Flat roof
    d) Madras terrace roof
12. The weight of rose wood after seasoning is _____.
    a) 7900 N/m^3 b) 6900 N/m^3 c) 8600 N/m^3 d) 7700 N/m^3
13. The thickness of hard board is _____.
    a) 2 mm b) 3 mm c) 30 mm d) 5 mm

Civil_English_BM.indd 207 12/21/2019 5:30:35 PM