signals from the sensors and calculates the diesel injection pressure, injection timing, amount of fuel injected and the duration of injection etc. and gives output signals to the injectors. The electrical signals from the ECU operates the solenoid switch. Depending on the electrical signals received from the ECU the solenoid will open and close the injector hole and sprays the fuel. The limit switch and the non return valve in the common rail control the diesel pressure and the excess diesel is returned to the fuel tank.

9.12.1 Advantage of CRDI System

1. Improves the engine's performance
2. Reduces the diesel supplied
3. Reduces the emissions
4. Improve the power output
5. Starts the engine quickly
6. Smooth engine operation

Student Activity

1. Students should prepare a report on the rich mixture, lean mixture and normal mixture used in two-wheeler engines.
2. Students should visit the nearby workshops to study the process fuel combustion in an IC engine and should submit a report with the sketch of float chamber, carburettor and AC mechanical pump.

Glossary

Convergent	-	தரமாற்றிக் கொள்ளுதல்
Ventury	-	குறுகிய
Vaporized	-	ஆவியாதல்
Intel Mani Fold	-	உட்செல்லும் வழி
Vacuum	-	வெற்றிடம்
Multi Point Fuel Injection	-	பல துளைகள் கொண்ட எரி பொருள் உமிழ்ப்பான்
Electronic Control Unit	-	மின்னணு கட்டுப்பாட்டுக் கருவி
OTTO Cycle	-	ஆட்டோ சுழற்சி
Centrifugal	-	மைய விலக்கு
Governor	-	செயல் கட்டுப்பாட்டுக் கருவி

AM_Unit_09.indd 196 31-01-2019 18:02:31