- It is used to lift the four-wheeler to a certain height.
- The vehicle is lifted and supported by the use of this screw jack.
- With the help of this, damages on the bottom side of the vehicle are cleared and it is available in many sizes depends on the weight of the vehicle.

Horses

After lifting the screw jack to a certain height, horses have to be lifted to the same level and then the cotter pin has to be inserted. With the use of this horse, the screw jack has been removed.

It has been used depends on the weight of the vehicle. For to support the vehicle with high load, low load capacity horse should not be used. Fig 2.3.7(b) shows the diagram of Horse.



Figure 2.3.7(b) Horses

2.3.8 HYDRAULIC POWER TOOLS

In automobile industries, the work should be carried out in careful and in an unmistakable manner. In doing that, small defects in the vehicles are repaired by using hand tools. In sometimes, large defects are repaired by removing the particular defected components from the vehicle and moving down the removed components to the ground or to the bench and then repaired. Similarly, sometimes the parts located below the chassis have to be repaired, that time the vehicle is lifted to a particular height and then repaired. For this purpose, power tools are used in the automotive industries. This is due to that weight of the vehicle is high and repairing the components underneath the vehicle is complicated and too risky. Power tools are utilized depends on the nature of work. The following are some classification of power tools.

2.3.8(a) Hydraulic Crane

It is used to lift and unlift the heavy weight components like engine in an automotive vehicle and to shift the heavy weight components from one place to another place. Fig 2.3.8(a) shows Hydraulic Crane.



Figure 2.3.8(a) Hydraulic Crane

2.3.8(b) Hydraulic Jack

It works on the basic principle of Pascal's law. It is used to hold the heavyweight components in particular height and to move

AM_Unit_02.indd 48 12/20/2019 4:25:30 PM