30 values or ranges representing the values to be counted.

Example

The entries 2, 4, 6 and eight in the Value 1 ... 4 fields are to be counted.

=COUNT (2;4;6;"eight") = 3. The count of numbers is therefore 3. Text is ignored.

COUNTA(Value1; Value2; ... Value30)

Counts how many values are in the list. Text entries are also counted, even when they contain an empty string of length 0. Value1; Value2; ... Value30 are 1 to 30 arguments representing the values to be counted.

Example

The entries 2, 4, 6 and eight in the Value 1 ... 4 fields are to be counted.

=COUNTA(2;4;6;"eight") = 4. The count of values is therefore 4.

CORREL(Data1; Data2)

Returns the correlation coefficient between two data sets.Data1 is the first data set. Data2 is the second data set.

Example

=CORREL(A1:A20;B1:B20) calculates the correlation coefficient as a measure of the linear correlation of the two data sets.

LARGE(Data; Rank_C)

Returns the Rank_c-th largest value in a data set. Data is the cell range of data. Rank_C is the ranking of the value.

Example

=LARGE(A1:C50;2) gives the second largest value in the range A1:C50.

SMALL(Data; Rank_C)

Returns the Rank_c-th smallest value in a data set. Data is the cell range of data. Rank_C is the rank of the value.

Example

=SMALL(A1:C50;3) gives the third smallest value in the range A1:C50.

AVERAGE(Number1; Number2; ... Number20)

Returns the average of the arguments. Number1; Number2; ... Number20.

Example

=AVERAGE(A1:A20) returns the average of set of values in the cell range A1:A20

10.11.4 – Working with the functions in Logical Category.

IF (Test; TrueValue; FalseValue)

Specifies a logical test to be performed. Test is any value or expression that can be TRUE or FALSE. TrueValue (optional) is the value that is returned if the logical test is TRUE. FalseValue (optional) is the value that is returned if the logical test is FALSE.