6. If $A=\begin{bmatrix} 8 & -4 \\ -5 & 3 \end{bmatrix}$, verify that $A(\text{adj } A)=(\text{adj } A)A=|A|I_2$.

7. If $A=\begin{bmatrix} 3 & 2 \\ 7 & 5 \end{bmatrix}$ and $B=\begin{bmatrix} -1 & -3 \\ 5 & 2 \end{bmatrix}$, verify that $(AB)^{-1}=B^{-1}A^{-1}$.

8. If $\text{adj}(A)=\begin{bmatrix} 2 & -4 & 2 \\ -3 & 12 & -7 \\ -2 & 0 & 2 \end{bmatrix}$, find A.

9. If $\text{adj}(A)=\begin{bmatrix} 0 & -2 & 0 \\ 6 & 2 & -6 \\ -3 & 0 & 6 \end{bmatrix}$, find A^{-1}.

10. Find $\text{adj}(\text{adj}(A))$ if $\text{adj } A=\begin{bmatrix} 1 & 0 & 1 \\ 0 & 2 & 0 \\ -1 & 0 & 1 \end{bmatrix}$.

11. $A=\begin{bmatrix} 1 & \tan x \\ -\tan x & 1 \end{bmatrix}$, show that $A^T A^{-1}=\begin{bmatrix} \cos 2x & -\sin 2x \\ \sin 2x & \cos 2x \end{bmatrix}$.

12. Find the matrix A for which $A\begin{bmatrix} 5 & 3 \\ -1 & -2 \end{bmatrix}=\begin{bmatrix} 14 & 7 \\ 7 & 7 \end{bmatrix}$.

13. Given $A=\begin{bmatrix} 1 & -1 \\ 2 & 0 \end{bmatrix}$, $B=\begin{bmatrix} 3 & -2 \\ 1 & 1 \end{bmatrix}$ and $C=\begin{bmatrix} 1 & 1 \\ 2 & 2 \end{bmatrix}$, find a matrix X such that $AXB=C$.

14. If $A=\begin{bmatrix} 0 & 1 & 1 \\ 1 & 0 & 1 \\ 1 & 1 & 0 \end{bmatrix}$, show that $A^{-1}=\frac{1}{2}\left(A^2-3I\right)$.

15. Decrypt the received encoded message $\begin{bmatrix} 2 & -3 \end{bmatrix}\begin{bmatrix} 20 & 4 \end{bmatrix}$ with the encryption matrix $\begin{bmatrix} -1 & -1 \\ 2 & 1 \end{bmatrix}$ and the decryption matrix as its inverse, where the system of codes are described by the numbers 1-26 to the letters $A-Z$ respectively, and the number 0 to a blank space.

1.3 Elementary Transformations of a Matrix

A matrix can be transformed to another matrix by certain operations called elementary row operations and elementary column operations.

1.3.1 Elementary row and column operations

Elementary row (column) operations on a matrix are as follows:

(i) The interchanging of any two rows (columns) of the matrix

(ii) Replacing a row (column) of the matrix by a non-zero scalar multiple of the row (column) by a non-zero scalar.

(iii) Replacing a row (column) of the matrix by a sum of the row (column) with a non-zero scalar multiple of another row (column) of the matrix.

Chapter 1 Matrices.indd 16 31-01-2020 17:12:43