$$I\frac{d^2\theta}{dt^2} = -p_m B\sin\theta$$

The negative sign implies that both are in opposite directions. The above equation can be written as

$$\frac{d^2\theta}{dt^2} = -\frac{p_m B}{I}\sin\theta$$

This is non-linear second order homogeneous differential equation. In order to make it linear, we use small angle approximation as we did in XI volume II (Unit 10 – oscillations, Refer section 10.4.4) i.e., $\sin\theta \approx \theta$, we get

$$\frac{d^2\theta}{dt^2} = -\frac{p_m B}{I}\theta$$

This linear second order homogeneous differential equation is a Simple Harmonic differential equation.

Comparing this equation with Simple Harmonic Motion (SHM) differential equation

$$\frac{d^2x}{dt^2} = -\omega^2 x$$

where ω is the angular frequency of the oscillation. Therefore,

$$\omega^2 = \frac{p_m B}{I} \Rightarrow \omega = \sqrt{\frac{p_m B}{I}}$$

$$T = 2\pi\sqrt{\frac{I}{p_m B}}$$

$$T = 2\pi\sqrt{\frac{I}{p_m B_H}} \text{ in second}$$

where B_H is the horizontal component of Earth's magnetic field.

Note

1. The current in circuit can be calculated from I = K tan θ, where K is called reduction factor of tangent Galvanometer, where

$$K = \frac{2RB_H}{\mu_o N}$$


2. Sensitivity measures the change in the deflection produced by a unit current, mathematically

$$\frac{d\theta}{dI} = \frac{1}{K\left(1+\frac{I^2}{K^2}\right)}$$

3. The tangent Galvanometer is most sensitive at a deflection of 45°. Generally the deflection is taken between 30°

EXAMPLE A3.2

Calculate the magnetic field at a point P which is perpendicular bisector to current carrying straight wire as shown in figure.



Appendix-1.indd 323 14-02-2020 20:14:36