### Solution

Let the length MN = y and the point P is on its perpendicular bisector. Let O be the point on the conductor as shown in figure.

Therefore, $OM = ON = \frac{y}{2}$, then

$$\cos\varphi_1 = \frac{adjacent\,length}{hypotenuse\,length} = \frac{ON}{PN}$$

$$= \frac{\frac{y}{2}}{\sqrt{\frac{y^2}{4}+a^2}} = \frac{y}{\sqrt{y^2+4a^2}}$$

$$\cos(\pi-\varphi_2) = \frac{adjacent\,length}{hypotenuse\,length} = \frac{OM}{PM}$$

$$\cos\varphi_2 = -\frac{OM}{PM}$$

Using the equation,

$$\vec{B} = \frac{\mu_\circ I}{4\pi a}(\cos\varphi_1 - \cos\varphi_2)\hat{n}$$

We get $\vec{B} = \frac{\mu_\circ I}{4\pi a}\frac{2y}{\sqrt{y^2+4a^2}}\hat{n}$

For long straight wire, $y \to \infty$,

$$\vec{B} = \frac{\mu_\circ I}{2\pi a}\hat{n}$$


The result obtained is same as we obtained in equation (3.39).

## EXAMPLE A3.3

Show that for a straight conductor, the magnetic field

$$\vec{B} = \frac{\mu_\circ I}{4\pi a}(\cos\varphi_1 - \cos\varphi_2)\hat{n}$$

$$= \frac{\mu_\circ I}{4\pi a}(\sin\theta_1 + \sin\theta_2)\hat{n}$$




### Solution:

In a right angle triangle OPN, let the angle $\angle OPN = \theta_1$ which implies, $\varphi_1 = \frac{\pi}{2} - \theta_1$ and also in a right angle triangle OPM, $\angle OPM = \theta_2$ which implies, $\varphi_2 = \frac{\pi}{2} + \theta_2$

Hence,

$$\vec{B} = \frac{\mu_\circ I}{4\pi a}\left(\cos\left(\frac{\pi}{2}-\theta_1\right) - \cos\left(\frac{\pi}{2}+\theta_2\right)\right)\hat{n}$$

$$= \frac{\mu_\circ I}{4\pi a}(\sin\theta_1 + \sin\theta_2)\hat{n}$$

## EXAMPLE A3.4

Consider a circular wire loop of radius R, mass m kept at rest on a rough surface. Let I be the current flowing through the loop and $\vec{B}$ be the magnetic field acting along horizontal as shown in Figure. Estimate the current I that should be applied so that one edge of the loop is lifted off the surface?



Appendix-1.indd 324 14-02-2020 20:14:40