3. With the help of megger, test the leakage in the appliance.
4. Remove the bottom cover which contains heating element, thermostat and indicating lamp.
5. Remove the earth connection from the body of the geyser.
6. Remove the fitting clamps of the geyser.
7. Check the continuity of the heating element.
8. After removing the heating element, clean the scale formation by using hydro chloric acid solution.

After verification of all these above, ensure that all the parts and materials of the geyser are in good condition.

Assembling procedure

1. Check it the geyser is clean and fit it with clamps.
2. Connect the earth wire with the body of the geyser.
3. Fit the bottom cover of the geyser properly. (In this heating element, thermostat and indicating lamp are fixed)
4. With the help of megger, check out the electrical leakage, if any.
5. Then connect the electrical supply to the geyser and make sure that it was connected properly and firmly.

Observations made after completion of installation or fitting of the geyser

1. After installation of the geyser, open the inlet tap of the control valve, until the water tank is filled.
2. Switch 'on' the supply and wait for few minutes and then open the hot water tap.
3. Check the continuous flow of warm water is coming properly.
4. Close the tap of hot water when not in use and turn off the supply

	Open circuit	Short circuit	Earthing
Test lamp	Won't glow / Glow	Bright / Dim	Glow / Won't glow
Fault	Occurred / Not occurred	Occurred / Not occurred	Occurred / Not occurred

Observation record

a. Voltage of the geyser :
b. Storage capacity of the geyser :
c. Power supply of the geyser :
d. Frequency supply of the geyser :
e. Current of the geyser :
f. Fuse rating :

BEE_ENG_Pratical.indd 184 12/27/2019 10:54:34 AM