5. In which function the soap powder is removed in the clothes?
   a) Washing function
   b) Rinsing function
   c) Dryer function
   d) Exhaust function

6. How many drums are in semi-automatic washing machine
   a) 1
   b) 2
   c) 1 or 2
   d) 3

7. Which part is used to produce centrifugal force
   a) Scroll cover
   b) Blocking box
   c) Shaft
   d) Impeller

8. The purpose of the gland packing rope is to
   a) Prevent impeller from coming out
   b) Prevent leakage of water from the casing near the spindle
   c) Provide lubrication to the spindle
   d) Prevent air leakage from the casing.

9. Impeller is made up of
   a) Galvanized steel.
   b) Brass.
   c) Cast iron or gun metal.
   d) Copper metal alloy.

10. Velocity imparted by the impeller to the water is converted to pressure by the
    a) Casing or volute
    b) Stuffing box
    c) Spindle
    d) Gland box

11. Maximum suction lift that is possible for water is
    a) 24 feet
    b) 28 feet
    c) 34 feet
    d) 38 feet

12. To ensure that the pump remains always primed it is necessary to have
    a) valve on delivery side should be open
    b) suction side should not be kept open
    c) foot valve is not leaking
    d) gland packing should not be leaking.

13. When using automatic operation of the pump, it should be ensured that
    a) water level is always above the foot valve
    b) delivery valve is closed at the time of starting
    c) suction side is not less than 20 feet.
    d) water level is always below the foot value.

BEE_ENG_Chapter_04.indd 71 12/27/2019 10:27:25 AM