10. Wet Weather Flow

It is the normal flow of sewage during the rainy season of the year.

11. Sludge

It is the organic matter deposited at the bottom of the sedimentation tank during the treatment of sewage.

5.2 Collection and Conveyance of Refuse

The two methods which are mainly adopted for the collection and disposal of refuse are as follows

1. Dry (or) Conservancy system
2. Water carriage system

5.2.1 Systems of Sanitation

1. Dry or Conservancy System

In this system garbage is collected, carried and disposed off by burning or burying. Sullage is collected in open drain and let off in natural water bodies. Night soil is removed by labour and conveyed outside the town to form manure.

2. Water carriage System

It is the most hygienic system. In this system, sewage is collected in a system of pipes and transported for treatment and disposed in a harmless manner without causing any nuisance.

Merits

1. It is hygienic.
2. No labour is required.
3. Maintenance cost is low.
4. Collection and conveyance is easy even in multi-storeyed buildings.
5. Modern methods of treatment can be given in this system.

Demerits

1. Needs large quantity of water.
2. Initial cost of construction is high.



Histroy of sanitation

1854: Dr John Snow showed that cholera was spread by water. **1860**: The first septic tank was constructed by Louis Moureas and used by communities to remove solids from waste water before the liquid was discharged into water body. This design was improved by use of trickling sand filtration from **1893**.

5.2.2 Systems of Sewerage

The three systems of sewerage are as follows

1. Separate system
2. Combined system
3. Partially separate system

1. Separate System

In this system two sets of sewers are laid. One for carrying sewage and another for carrying storm water. The sewage is carried to the treatment plant and the storm water is directly discharged into outlet in the form of river (or) stream.

2. Combined System

In this system, only one sewer is laid and it carries both sewage and storm water. The sewage and storm water are carried to the sewage treatment plant.

3. Partially Separate System

In this system, arrangement is made to permit early washings by rain into sewer carrying sewerage. When the quantity of storm water exceeds a particular limit it is collected and conveyed in open drains to the natural river (or) stream.

U5.indd 88 12/11/2019 1:03:04 PM