


The person who drives the car doesn't care about the internal working. To increase the speed of the car he just presses the accelerator to get the desired behaviour. Here the accelerator is the interface between the driver *(the calling / invoking object)* and the engine *(the called object)*.

In this case, the function call would be Speed (70): This is the interface.

Internally, the engine of the car is doing all the things. It's where fuel, air, pressure, and electricity come together to create the power to move the vehicle. All of these actions are separated from the driver, who just wants to go faster. Thus we separate interface from implementation.

Let us see a simple example, consider the following implementation of a function that finds the minimum of its three arguments:

```
let min 3 x y z :=
        if x < y then
                if x < z then x else z
        else
                if y < z then y else z
```

1.4 Pure functions

Pure functions are functions which will give exact result when the same arguments are passed. For example the mathematical function sin (0) always results **0**. This means that every time you call the function with the same arguments, you will always get the same result. A function can be a pure function provided it should not have any external variable which will alter the behaviour of that variable.

Let us see an example

```
let square x
        return: x * x
```

The above function square is a pure function because it will not give different results for same input.

There are various theoretical advantages of having pure functions. One advantage is that if a function is pure, then if it is called several times with the same arguments, the compiler only needs to actually call the function once. Lt's see an example

```
let i: = 0;
        if i <strlen (s) then
        -- Do something which doesn't affect s
        ++i
```


XII Std - CS EM Chapter-1.indd 4 24-01-2020 12:38:55