7.5.4 Variable-Length Arguments

In some instances you might need to pass more arguments than have already been specified. Going back to the function to redefine it can be a tedious process. Variable-Length arguments can be used instead. These are not specified in the function's definition and an asterisk (*) is used to define such arguments.

Lets see what happens when we pass more than 3 arguments in the sum() function.

Example:

```
def sum(x,y,z):
        print("sum of three nos :",x+y+z)
sum(5,10,15,20,25)
```

When the above code is executed, it produces the following **result** :

TypeError: sum() takes 3 positional arguments but 5 were given

7.5.4.1 Syntax - Variable-Length Arguments

```
def function_name(*args):
        function_body
        return_statement
```

Example:

```
def printnos (*nos):
        for n in nos:
        print(n)
        return
# now invoking the printnos() function
print ('Printing two values')
printnos (1,2)
print ('Printing three values')
printnos (10,20,30)
```

Output:

```
Printing two values
        1
        2
Printing three values
        10
        20
        30
```

Evaluate Yourself



In the above program change the function name printnos as printnames in all places wherever it is used and give the appropriate data Ex. printnos (10, 20, 30) as printnames ('mala', 'kala', 'bala') and see output.

XII Std - CS EM Chapter-7.indd 96 24-01-2020 11:03:49