Example

```
num1=int (input("Number 1: "))
num2=int (input("Number 2: "))
print ("The sum of { } and { } is { }".format(num1, num2,(num1+num2)))
```

Out Put

```
Number 1: 34
Number 2: 54
The sum of 34 and 54 is 88
```

8.9 Built-in String functions

Python supports the following built-in functions to manipulate string.

Syntax	Description	Example

len(str)	Returns the length (no of characters) of the string.	>>> A="Corporation"
		>>> print(len(A))
		11

capitalize( )	Used to capitalize the first character of the string	>>> city="chennai"
		>>> print(city.capitalize())
		Chennai

center(width, fillchar)	Returns a string with the original string centered to a total of width columns and filled with fillchar in columns that do not have characters	>>> str1="Welcome"
		>>> print(str1.center(15,'*'))
		********Welcome*******

find(sub[, start[, end]])	The function is used to search the first occurrence of the sub string in the given string. It returns the index at which the substring starts. It returns -1 if the substring does not occur in the string.	>>>str1='mammals' >>>str1.find('ma') ***0*** ***On omitting the start parameters, the function starts the search from the beginning.*** >>>str1.find('ma',2) 3 >>>str1.find('ma',2,4) -1 ***Displays -1 because the substring could not be found between the index 2 and 4-1.*** >>>str1.find('ma',2,5) 3

XII Std - CS EM Chapter-8.indd 123 24-01-2020 11:18:43