Syntax	Description	Example

count(str, beg, end)	Returns the number of substrings occurs within the given range. Remember that substring may be a single character. Range (beg and end) arguments are optional. If it is not given, python searched in whole string. Search is case sensitive.	>>> str1="Raja Raja Chozhan"
		>>> print(str1.count('Raja'))
		2
		>>> print(str1.count('r'))
		0
		>>> prin***t(str1.count('R'))***
		2
		>>> print(str1.count('a'))
		5
		>>> print(str1.count('a',0,5))
		2
		>>> print(str1.count('a',11))
		1

ord(char)	Returns the ASCII code of the character.	>>> ch = 'A'
		>>> print(ord(ch))
		65
		>>> print(***ord('B'))***
		66

chr(ASII)	Returns the character represented by a ASCII.	>>> ch=97
		>>> print(chr(ch))
		a
		>>> print(chr(87))
		W

8.10 Membership Operators

The '**in**' and '**not in**' operators can be used with strings to determine whether a string is present in another string. Therefore, these operators are called as Membership Operators.

Example

```
str1=input ("Enter a string: ")
str2="chennai"
if str2 in str1:
        print ("Found")
else:
        print ("Not Found")
```

Output : 1

```
Enter a string: Chennai G HSS, Saidapet
Found
```

Output : 2

```
Enter a string: Govt G HSS, Ashok Nagar
Not Found
```


XII Std - CS EM Chapter-8.indd 125 24-01-2020 11:18:43