5. Write a program that reverse a list using a loop.
6. Write a program to insert a value in a list at the specified location.
7. Write a program that creates a list of numbers from 1 to 50 that are either divisible by 3 or divisible by 6.
8. Write a program to create a list of numbers in the range 1 to 20. Then delete all the numbers from the list that are divisible by 3.
9. Write a program that counts the number of times a value appears in the list. Use a loop to do the same.
10. Write a program that prints the maximum and minimum value in a dictionary.

Evaluation

GL6J6X

Part - I

Choose the best answer **(1 Marks)**

1. Pick odd one in connection with collection data type

   (a) List (b) Tuple (c) Dictionary (d) Loop

2. Let list1=[2,4,6,8,10], then print(List1[-2]) will result in

   (a) 10 (b) 8 (c) 4 (d) 6

3. Which of the following function is used to count the number of elements in a list?

   (a) count() (b) find() (c)len() (d) index()

4. If List=[10,20,30,40,50] then List[2]=35 will result

   (a) [35,10,20,30,40,50] (b) [10,20,30,40,50,35]

   (c) [10,20,35,40,50] (d) [10,35,30,40,50]

5. If List=[17,23,41,10] then List.append(32) will result

   (a) [32,17,23,41,10] (b) [17,23,41,10,32]

   (c) [10,17,23,32,41] (d) [41,32,23,17,10]

6. Which of the following Python function can be used to add more than one element within an existing list?

   (a) append() (b) append_more() (c)extend() (d) more()

7. What will be the result of the following Python code?

   S=[x**2 for x in range(5)]