In the above code, the name of the class is Sample. Inside the class, we have assigned the variables **x** and **y** with initial value **10** and **20** respectively. These two variables are called as class variables or member variables of the class. In class instantiation process, we have created an object **S** to access the members of the class. The first two print statements simply print the value of class variable **x** and **y** and the last print statement add the two values and print the result.

10.5 Class Methods

Python class function or Method is very similar to ordinary function with a small difference that, the class method must have the first argument named as **self**. No need to pass a value for this argument when we call the method. Python provides its value automatically. Even if a method takes no arguments, it should be defined with the first argument called **self**. If a method is defined to accept only one argument it will take it as two arguments ie. self and the defined argument.

When you declare class variable within class, methods must be prefixed by the class name and dot operator.

Note

The statements defined inside the class must be properly indented.

Example 10.2: Program to find total and average marks using class

```
class Student:
    mark1, mark2, mark3 = 45, 91, 71        #class variable

    def process(self):                      #class method
        sum = Student.mark1 + Student.mark2 + Student.mark3
        avg = sum/3
        print("Total Marks = ", sum)
        print("Average Marks = ", avg)
        return

S=Student()
S.process()
```

In the above program, after defining the class, an object S is created. The statement S.process( ), calls the function to get the required output.

XII Std - CS EM Chapter-10.indd 172 24-01-2020 12:42:35