Note that, we have declared three variables mark1, mark2 and mark3 with the values 45, 91, 71 respectively. We have defined a method named **process** with **self** argument, which means, we are not going to pass any value to that method. First, the process method adds the values of the class variables, stores the result in the variable sum, finds the average and displays the result.

Thus the above code will show the following output.

Output

Total Marks = 207

Average Marks = 69.0

Example : program to check and print if the given number is odd or even using class

```
class Odd_Even:
    def check(self, num):
        if num%2==0:
        print(num," is Even number")
    else:
        print(num," is Odd number")
n=Odd_Even()
x = int(input("Enter a value: "))
n.check(x)
```

When you execute this program, Python accepts the value entered by the user and passes it to the method check through object.

Output 1

```
Enter a value: 4
4  is Even number
```

Output 2

```
Enter a value: 5
5  is Odd number
```

10.6 Constructor and Destructor in Python

Constructor is the special function that is automatically executed when an object of a class is created. In Python, there is a special function called **"init"** which act as a Constructor. It must begin and end with double underscore. This function will act as an ordinary function; but only difference is, it is executed automatically when the object is created. This constructor function can be defined with or without arguments. This method is used to initialize the class variables.

XII Std - CS EM Chapter-10.indd 173 24-01-2020 12:42:35