In the above program, class variable **num** is shared by all three objects of the class Sample. It is initialized to zero and each time an object is created, the num is incremented by 1. Since, the variable shared by all objects, change made to num by one object is reflected in other objects as well. Thus the above program produces the output given below.

Output

```
The object value is          =    15
The count of object created  =    1
The object value is          =    35
The count of object created  =    2
The object value is          =    45
The count of object created  =    3
```

***Note:* class variable is similar to static type in C++**

Destructor is also a special method gets executed automatically when an object exit from the scope. It is just opposite to constructor. In Python, __del__( ) method is used as destructor.

Example : Program to illustrate about the __del__( ) method

```
class Sample:
        num=0
        def __init__(self, var):
                Sample.num+=1
                self.var=var
                print("The object value is = ", var)
                print("The value of class variable is= ", Sample.num)
        def __del__(self):
                Sample.num-=1
                print("Object with value %d is exit from the scope"%self.var)
S1=Sample(15)
S2=Sample(35)
S3=Sample(45)
```

10.7 Public and Private Data Members

The variables which are defined inside the class is public by default. These variables can be accessed anywhere in the program using dot operator.

A variable prefixed with double underscore becomes private in nature. These variables can be accessed only within the class.

XII Std - CS EM Chapter-10.indd 175 24-01-2020 12:42:36