Example showing **DEFAULT** Constraint in the student table:

```
CREATE TABLE Student
(
Admno integer    NOT NULL  PRIMARY KEY,
Name char(20)NOT NULL,
Gender char(1),
Age integer  DEFAULT = "17", → Default Constraint
Place char(10),
);
```

In the above example the "Age" field is assigned a default value of 17, therefore when no value is entered in age by the user, it automatically assigns 17 to Age.

12.7.2.4 Check Constraint

This constraint helps to set a limit value placed for a field. When we define a check constraint on a single column, it allows only the restricted values on that field. Example showing check constraint in the student table:

```
CREATE TABLE Student
(
Admno integer    NOT NULL PRIMARY KEY
Name char(20)NOT NULL,
Gender char(1),
Age integer CHECK (Age <=19), → Check Constraint
Place char(10),
);
```

In the above example the check constraint is set to Age field where the value of Age must be less than or equal to 19.

Note

The check constraint may use relational and logical operators for condition.

12.7.2.5 TABLE CONSTRAINT

When the constraint is applied to a group of fields of the table, it is known as Table constraint. The table constraint is normally given at the end of the table definition. Let us take a new table namely Student1 with the following fields Admno, Firstname, Lastname, Gender, Age, Place:

XII Std - CS EM Chapter-12.indd 214 24-01-2020 11:20:32