12.7.3.3 UPDATE COMMAND

The **UPDATE** command updates some or all data values in a database. It can update one or more records in a table. The **UPDATE** command specifies the rows to be changed using the **WHERE** clause and the new data using the **SET** keyword. The command is used as follows:

UPDATE <table-name> SET column-name = value, column-name = value,… WHERE condition;

For example to update the following fields:

UPDATE Student SET Age = 20 WHERE Place = "Bangalore";

The above command will change the age to 20 for those students whose place is "Bangalore".

The table will be as updated as below:

Admno	Name	Gender	Age	Place
100	Ashish	M	17	Chennai
101	Adarsh	M	18	Delhi
102	Akshith	M	20	Bangalore
103	Ayush	M	18	Delhi

To update multiple fields, multiple field assignment can be specified with the **SET** clause separated by comma. For example to update multiple fields in the Student table, the command is given as:

UPDATE Student SET Age=18, Place = 'Chennai' WHERE Admno = 102;

102	Akshith	M	18	Chennai

The above command modifies the record in the following way.

Admno	Name	Gender	Age	Place
100	Ashish	M	17	Chennai
101	Adarsh	M	18	Delhi
102	Akshith	M	18	Chennai
103	Ayush	M	18	Delhi

12.7.4 Some Additional DDL Commands:

12.7.4.1 ALTER COMMAND

The **ALTER** command is used to alter the table structure like adding a column, renaming the existing column, change the data type of any column or size of the column or delete the column from the table. It is used in the following way :

ALTER TABLE <table-name> ADD <column-name><data type><size>;

XII Std - CS EM Chapter-12.indd 217 24-01-2020 11:20:32