can also be used to connect search conditions in the **WHERE** clause. For example :

SELECT Admno, Name, Age, Place FROM Student WHERE (Age>=18 AND Place = "Delhi");

Admno	Name	Age	Place
101	Adarsh	18	Delhi
103	Ayush	18	Delhi

The **SELECT** command can also be used in the following ways:

SELECT Admno, Name, Age, Place FROM Student WHERE (Age>=18 OR Place ="Delhi");

SELECT Admno, Name, Place FROM Student WHERE (NOT Place ="Delhi");

12.7.5.3 BETWEEN and NOT BETWEEN Keywords

The **BETWEEN** keyword defines a range of values the record must fall into to make the condition true. The range may include an upper value and a lower value between which the criteria must fall into.

SELECT Admno, Name, Age, Gender FROM Student WHERE Age BETWEEN 18 AND 19;

Admno	Name	Gender	Age	Place
101	Adarsh	M	18	Delhi
103	Ayush	M	18	Delhi
104	Abinandh	M	18	Chennai
105	Revathi	F	19	Chennai
106	Devika	F	19	Bangalore

The **NOT BETWEEN** is reverse of the **BETWEEN** operator where the records not satisfying the condition are displayed.

SELECT Admno, Name, Age FROM Student WHERE Age NOT BETWEEN 18 AND 19;

Admno	Name	Age
100	Ashish	17
102	Akshith	17
107	Hema	17

12.7.5.4 IN Keyword

The **IN** keyword is used to specify a list of values which must be matched with the record values. In other words it is used to compare a column with more than one value. It is similar to an **OR** condition.

For example :

SELECT Admno, Name, Place FROM Student WHERE Place IN ("Chennai", "Delhi");

XII Std - CS EM Chapter-12.indd 222 24-01-2020 11:20:32