SELECT Gender, count(*) FROM Student GROUP BY Gender;

Gender	count(*)
M	5
F	3



Note

The * is used with the COUNT to include the NULL values.

The GROUP BY applies the aggregate functions independently to a series of groups that are defined by having a field value in common. The output of the above SELECT statement gives a count of the number of Male and Female students.

12.7.5.8 HAVING clause

The **HAVING** clause can be used along with GROUP BY clause in the SELECT statement to place condition on groups and can include aggregate functions on them. For example to count the number of Male and Female students belonging to Chennai .

SELECT Gender , count(*) FROM Student GROUP BY Gender HAVING Place = 'Chennai';

Gender	count(*)
M	2
F	2

The above output shows the number of Male and Female students in Chennai from the table student.

12.7.6 TCL commands

12.7.6.1 COMMIT command

The **COMMIT** command is used to permanently save any transaction to the database. When any DML commands like **INSERT, UPDATE, DELETE** commands are used, the changes made by these commands are not permanent. It is marked permanent only after the **COMMIT** command is given from the SQL prompt. Once the **COMMIT** command is given, the changes made cannot be rolled back. The **COMMIT** command is used as

```
COMMIT;
```

12.7.6.2 ROLLBACK command

The **ROLLBACK** command restores the database to the last commited state. It is used with **SAVEPOINT** command to jump to a particular savepoint location. The syntax for the **ROLLBACK** command is :

```
ROLL BACK TO  save point name;
```


XII Std - CS EM Chapter-12.indd 226 24-01-2020 11:20:33