The following program read the file through Python using "csv.reader()".

```
import csv
csv.register_dialect('myDialect',delimiter = ',',skipinitialspace=True)
F=open('c:\pyprg\sample2.csv','r')
reader = csv.reader(F, dialect='myDialect')
for row in reader:
        print(row)
F.close()
```

OUTPUT

```
['Topic1', 'Topic2', 'Topic3']
['one', 'two', 'three']
['Example1', 'Example2', 'Example3']
```

As you can see in "sample2.csv" there are spaces after the delimiter due to which the output is also displayed with spaces.

These whitespaces can be removed, by registering new dialects using **csv.register_dialect()** class of csv module. **A dialect describes the format of the csv file that is to be read.** In dialects the parameter **"skipinitialspace"** is used for removing whitespaces after the delimiter.

Note

By default "skipinitialspace" has a value false

The following program reads "sample2.csv" file, which contains spaces after the delimiter.

```
import csv
csv.register_dialect('myDialect',delimiter = ',',skipinitialspace=True)
F=open('c:\pyprg\sample2.csv','r')
reader = csv.reader(F, dialect='myDialect')
for row in reader:
        print(row)
F.close()
```

OUTPUT

```
['Topic1', 'Topic2', 'Topic3']
['one', 'two', 'three']
['Example1', 'Example2', 'Example3']
```


XII Std - CS EM Chapter-13.indd 244 24-01-2020 12:50:36