Python code	How does it works
import sys, os, getopt	include sys , os and getopt modules to use the required function
def main(argv):	Function main() is defined and 'argv' contains the 'input mode and the c++ program file' in the form of list i.e ['-i', 'c:\ pyprg \pali_cpp']
opts, args = getopt.getopt(argv, "i:")	getopt() splits the command as option and argument. 'opts' contains [('-i', 'c:\pyprg\pali_cpp')]. Since no error 'args' shows []
for o, a in opts:	'o' contains the mode and 'a' contains the path of c++ program i.e print("o = ",o) shows o = -i print("a = ",a) shows a = c:\pyprg\pali_cpp
if o in ("-i"):	Checks o == 'i' if true
run(a)	Calls the function run() passed along with the c++ program
def run(a):	Definition of run() function begins here
inp_file=a+'.cpp'	Variable 'inp_file' contains the joined c++ program name and .cpp print(inp_file) shows c:\pyprg\pali_cpp.cpp
exe_file=a+'.exe'	Variable 'exe_file' contains the joined c++ program name and .exe print(exe_file) shows c:\pyprg\pali_cpp.exe
os.system('g++ ' + inp_file + ' -o ' + exe_file)	g++ compiler compiles the c++ program in inp_file and store the executable file in exe_file
os.system(exe_file)	Executes the exe file
if __name__=='__main__':	__name__ stores name of the python program __ main__ also stores the name of the python program.
main(sys.argv[1:])	If 'name' and 'main' are equal then main() is called and passed with the command line argument omitting the python program name argv[1:] contains –i c:\pyprg\pali_cpp

XII Std - CS EM Chapter-14.indd 279 24-01-2020 11:33:49