Example 15.3.2 -1

```
import sqlite3
connection = sqlite3.connect ("Academy.db")
cursor = connection.cursor()
# if the table already exits then delete it using cursor.execute ("""DROP TABLE Student;""")
# where  Student is name of the table.
sql_command = """
CREATE TABLE Student (
Rollno INTEGER PRIMARY KEY , Sname VARCHAR(20), Grade CHAR(1),
gender CHAR(1), Average DECIMAL (5, 2), birth_date DATE);"""
cursor.execute(sql_command)
sql_command = """INSERT INTO Student (Rollno, Sname, Grade, gender, Average,
    birth_date) VALUES (NULL, "Akshay", "B", "M","87.8", "2001-12-12");"""
cursor.execute(sql_command)
sql_command = """INSERT INTO Student (Rollno, Sname, Grade, gender, Average,
    birth_date) VALUES (NULL, "Aravind", "A", "M","92.50","2000-08-17");"""
cursor.execute(sql_command)
# never forget this, if you want the changes to be saved:
connection.commit()
connection.close()
print("STUDENT TABLE CREATED")
```

OUTPUT

```
STUDENT TABLE CREATED
```

Of course, in most cases, you will not literally insert data into a SQL table. You will rather have a lot of data inside of some Python data type e.g. a dictionary or a list, which has to be used as the input of the insert statement.

The following working example, assumes that you have an already existing database Academy.db and a table Student. We have a list with data of persons which will be used in the INSERT statement:

XII Std - CS EM Chapter-15.indd 294 24-01-2020 12:52:57