If you run this program, saved as "sql_Academy_query.py", you would get the following result, depending on the actual data:

It should be noted that the database file that will be created will be in the same folder as that of the python file. If we wish to change the path of the file, change the path while opening the file.

Example 15.4.1-1

```
import sqlite3
#save the file as "sql_Academy_query.py"
# cursor object
crsr = connection.cursor()
# execute the command to fetch all the data from the table Student
crsr.execute("SELECT * FROM Student")
# store all the fetched data in the ans variable
ans= crsr.fetchall()
# loop to print all the data
for i in ans:
        print(i)
```

15.4.1.1 Displaying all records using fetchall()

The fetchall() method is used to fetch all rows from the database table

Example 15.4.1.1-1

```
import sqlite3
connection = sqlite3.connect("Academy.db")
cursor = connection.cursor()
cursor.execute("SELECT * FROM student")
print("fetchall:")
result = cursor.fetchall()
for r in result:
    print(r)
```

OUTPUT

```
fetchall:
(1, 'Akshay', 'B', 'M', 87.8, '2001-12-12')
(2, 'Aravind', 'A', 'M', 92.5, '2000-08-17')
(3, 'BASKAR', 'C', 'M', 75.2, '1998-05-17')
(4, 'SAJINI', 'A', 'F', 95.6, '2002-11-01')
(5, 'VARUN', 'B', 'M', 80.6, '2001-03-14')
(6, 'PRIYA', 'A', 'F', 98.6, '2002-01-01')
(7, 'TARUN', 'D', 'M', 62.3, '1999-02-01')
```


XII Std - CS EM Chapter-15.indd 296 24-01-2020 12:52:57