eval()	*This function is used to evaluate the value of a string.*
Father of Relational Database	*Dr. Edgar Frank Codd*
g++	*compiler to compile c++ program*
GIS	*Geographic Information System*
global Scope	*A variable, with global scope can be used anywhere in the program.*
Glue language	*You do not write the complete application in the language, but rather, you use the language to orchestrate(organize) modules written in (possibly many different) other languages, making them work together to form the application. A glue language makes it easy to do that (convenient syntax, good support for inter-process communication and data managing, no compilation step etc).*
id ()	*It returns the memory address of the given object.*
IDLE	*Integrated Development Environment*
immutable	*unchangeable*
Implementation	*Implementation carries out the operation declared in the interfac*
import	*Import in python is similar to #include header_file in C++. Python modules can get access to code from another module by importing the file/function using "import" statement.*
Impure Functions	*Any function that changes the internal state of one of its arguments or the value of some external variable is an impure function.*
Instantiation	*Process of creating an object*
Integrity	*Whole and undivided*
Interactive Mode	*A way of using the Python interpreter by typing command and expressions at the prompt.*
Interface	*Interface defines what an object can do, but doesn't actually do it*
interpreter	*Translates program one statement at a time. It continues translating the program until the first error is met, in which case it stops. Hence debugging is easy.*
Intersection	*Intersection defines a relation consisting of a set of all tuple that are in both A and B.*
Key	*Data that is mapped to a value in a dictionary*

XII Std - CS EM Glossary.indd 337 1/19/2020 10:49:50 AM