| | |
|---|---|
| *Queue* | *Queue is an abstract data structure, somewhat similar to Stacks. Unlike stacks, a queue is open at both its ends. One end is always used to insert data(enqueue) and the other is used to remove data(dequeue). Queue follows First-In-First-Out methodology, i.e., the data item stored first will be accessed first.* |
| *RDBMS* | *Relational Database Management System* |
| *recursion* | *When a function calls itself is known as recursion.* |
| *Redundant* | *Duplication of data* |
| *Routines* | *routines are otherwise called as functions or methods. In Python it is also called as definition* |
| *Schema* | *Structure or model* |
| *Scope* | *Visibility of variables, parameters and functions in one part of a program to another part of the same program.* |
| *Script* | *A Python program stored in a file.* |
| *Script Mode* | *A way of using the Python interpreter by typing command and expressions at the prompt.* |
| *Select ( σ )* | *The SELECT operation is used for selecting a subset of the tuples according to a given selection condition* |
| *Selectors* | *Functions that retrieve information from the data type.* |
| *Sequential* | *One after another* |
| *Set difference(-)* | *(-) symbol denotes it. The result of A-B is a relation which includes all tuples that are in A but not in B.* |
| *skipinitialspace=true* | *When true, whitespace immediately following the delimeter is ignored. The default is false* |
| *slicing* | *cut* |
| *Stack* | *A stack (sometimes called a "push-down stack") is an ordered collection of items where the addition of new items and the removal of existing items always takes place at the same end. This end is commonly referred to as the "top." The end opposite the top is known as the "base.This ordering principle is sometimes called LIFO, last- in first-out.* |
| *stride* | *a long step* |
| *string* | *sequence of letters, numbers or symbols* |
| *subscript* | *an index number* |



XII Std - CS EM Glossary.indd 339 1/19/2020 10:49:50 AM