istitle()	Checks for Titlecased String
isupper()	returns if all characters are uppercase characters
join()	Returns a Concatenated String
ljust()	returns left-justified string of given width
lower()	returns lowercased string
lstrip()	Removes Leading Characters
maketrans()	returns a translation table
partition()	Returns a Tuple
replace()	Replaces Substring Inside
rfind()	Returns the Highest Index of Substring
rindex()	Returns Highest Index of Substring
rjust()	returns right-justified string of given width
rpartition()	Returns a Tuple
rsplit()	Splits String From Right
rstrip()	Removes Trailing Characters
slice()	creates a slice object specified by range()
split()	Splits String from Left
splitlines()	Splits String at Line Boundaries
startswith()	Checks if String Starts with the Specified String
strip()	Removes Both Leading and Trailing Characters
swapcase()	swap uppercase characters to lowercase; vice versa
title()	Returns a Title Cased String
translate()	returns mapped charactered string
upper()	returns uppercased string
zfill()	Returns a Copy of The String Padded With Zeros

III. List Functions

Function	Description
append()	Add Single Element to The List
clear()	Removes all Items from the List
copy()	Returns Shallow Copy of a List
count()	returns occurrences of element in a list
extend()	Add Elements of a List to Another List
index()	returns smallest index of element in list
insert()	Inserts Element to The List
list() Function	creates list in Python
pop()	Removes Element at Given Index
remove()	Removes Element from the List
reverse()	Reverses a List
slice()	creates a slice object specified by range()
sort()	sorts elements of a list

Annexure I.indd 343 24-01-2020 11:21:44