- An identifier must start with an alphabet (A..Z or a..z) or underscore (_).
- Identifiers may contain digits (0 .. 9)
- Python identifiers are case sensitive i.e. uppercase and lowercase letters are distinct.
- Identifiers must not be a **python** keyword.
- Python does not allow punctuation character such as %,$, @ etc., within identifiers.

Example of valid identifiers

Sum, total_marks, regno, num1

Example of invalid identifiers

12Name, name$, total-mark, continue

5.7.2. Keywords

Keywords are special words used by Python interpreter to recognize the structure of program. As these words have specific meaning for interpreter, they cannot be used for any other purpose.

Table 5.1 Python's Keywords

False	class	finally	is	return
none	continue	for	lambda	try
True	def	from	nonlocal	while
and	del	global	not	with
as	elif	if	or	yield
assert	else	import	pass	None
break	except	in	raise	

5.7.3 Operators

In computer programming languages operators are special symbols which represent computations, conditional matching etc. The value of an operator used is called **operands**. Operators are categorized as Arithmetic, Relational, Logical, Assignment etc. Value and variables when used with operator are known as **operands**.

(i) Arithmetic operators

An arithmetic operator is a mathematical operator that takes two operands and performs a calculation on them. They are used for simple arithmetic. Most computer languages contain a set of such operators that can be used within equations to perform different types of sequential calculations.