`development` entry in `config/database.yml` tells Rails where to look for it. For SQLite 3 users, this'll be a file in the `storage` directory.)

Note that the command is too wide to fit comfortably on the page. To enter a command on multiple lines, put a backslash as the last character on all but the last line, and you'll be prompted for more input. Windows users need to substitute a caret (`^`) for the backslash at the end of the first line and a backslash for the forward slash in `bin/rails`:

```
depot> bin/rails generate scaffold Product \
         title:string description:text image:attachment price:decimal
  invoke  active_record
  create    db/migrate/20250420000001_create_products.rb
  create    app/models/product.rb
  invoke    test_unit
  create      test/models/product_test.rb
  create      test/fixtures/products.yml
  invoke  resource_route
   route    resources :products
  invoke  scaffold_controller
  create    app/controllers/products_controller.rb
  invoke    tailwindcss
  create      app/views/products
  create      app/views/products/index.html.erb
  create      app/views/products/edit.html.erb
  create      app/views/products/show.html.erb
  create      app/views/products/new.html.erb
  create      app/views/products/_form.html.erb
  create      app/views/products/_product.html.erb
  invoke    resource_route
  invoke    test_unit
  create      test/controllers/products_controller_test.rb
  create      test/system/products_test.rb
  invoke    helper
  create      app/helpers/products_helper.rb
  invoke      test_unit
  invoke    jbuilder
  create      app/views/products/index.json.jbuilder
  create      app/views/products/show.json.jbuilder
  create      app/views/products/_product.json.jbuilder
```