OK, all the groundwork has been done. We set up our Depot application as a Rails project. We created the development database and configured our application to be able to connect to it. We created a products controller and a `Product` model and used a migration to create the corresponding `products` table. And a number of views have been created for us. It's time to see all this in action.

Seeing the List of Products

With four commands, we've created an application and a database (or a table inside an existing database if you chose something else besides SQLite 3) and installed Active Storage. Before we worry too much about what happened behind the scenes here, let's try our shiny new application.

We mentioned previously that using a CSS processor will affect how we start our server during development. This is because things like CSS processors and JavaScript bundlers require a build step. Rather than requiring you to start multiple processes, Rails provides `bin/dev`, which is a small script that will start everything:

```
depot> bin/dev
Installing foreman...
Fetching foreman-0.88.1.gem
Successfully installed foreman-0.88.1
Parsing documentation for foreman-0.88.1
Installing ri documentation for foreman-0.88.1
Done installing documentation for foreman after 0 seconds
1 gem installed
08:43:51 web.1  | started with pid 31227
08:43:51 css.1  | started with pid 31228
08:43:52 web.1  | => Booting Puma
08:43:52 web.1  | => Rails 8.0.2 application starting in development
08:43:52 web.1  | => Run `bin/rails server --help` for more startup options
08:43:52 web.1  | Puma starting in single mode...
08:43:52 web.1  | * Puma version: 6.5.0 ("Sky's Version")
08:43:52 web.1  | * Ruby version: ruby 3.4.3 (2024-12-25 revision
48d4efcb85)
08:43:52 web.1  | *  Min threads: 3
```