```
08:43:52 web.1  | *  Max threads: 3
08:43:52 web.1  | *  Environment: development
08:43:52 web.1  | *          PID: 31227
08:43:52 web.1  | * Listening on http://127.0.0.1:3000
08:43:52 web.1  | * Listening on http://[::1]:3000
08:43:52 web.1  | Use Ctrl-C to stop
08:43:52 css.1  |
08:43:52 css.1  | Rebuilding...
08:43:53 css.1  |
08:43:53 css.1  | Done in 228ms.
```

Note that in some environments, you may need `sudo` to install `foreman`. If so, run `sudo gem install foreman` and rerun the `bin/dev` command. Windows Powershell and Command Prompt users will need to run the command `ruby bin\dev`.

If you examine that output, in addtion to the lines containing `web.1` that show the Rails server starting, you see lines containing `css.1` that show the CSS rebuilding. This is all controlled by a file named `Procfile.dev`:

rails80/depot_a/Procfile.dev

```
web: bin/rails server
css: bin/rails tailwindcss:watch
```

Feel free to modify this file to suit your needs. For example, if you're using a virtual machine, you might need to add `-b 0.0.0.0` to the `rails server` line to accept connections from your host.

As with our demo application, this command starts a web server on our local host, port 3000. If you get an error saying `Address already in use` when you try to run the server, that means you already have a Rails server running on your machine. If you've been following along with the examples in the book, that might well be the Hello, World! application from Chapter 4. Find its console and kill the server using `Ctrl-C`. If you're running on Windows, you might see the prompt `Terminate batch job (Y/N)?`. If so, respond with `y`.