Iteration C1: Creating the Catalog Listing

We've already created the products controller, used by the seller to administer the Depot application. Now it's time to create a second controller, one that interacts with the paying customers. Let's call it `Store`:

```
depot> bin/rails generate controller Store index
   create  app/controllers/store_controller.rb
    route  get 'store/index'
   invoke  tailwindcss
   create    app/views/store
   create    app/views/store/index.html.erb
   invoke  test_unit
   create    test/controllers/store_controller_test.rb
   invoke  helper
   create    app/helpers/store_helper.rb
   invoke    test_unit
```

As in the previous chapter, where we used the `generate` utility to create a controller and associated scaffolding to administer the products, here we've asked it to create a controller (the `StoreController` class in the `store_controller.rb` file) containing a single action method, `index`.

While everything is already set up for this action to be accessed via http://localhost:3000/store/index (feel free to try it!), we can do better. Let's simplify things and make this the root URL for the website. We do this by editing `config/routes.rb`:

rails80/depot_d/config/routes.rb

```
  Rails.application.routes.draw do
»   root "store#index", as: "store_index"
    resources :products
    # Define your application routes per the DSL in
    # https://guides.rubyonrails.org/routing.html

    # Reveal health status on /up that returns 200 if the app boots with no
    # exceptions, otherwise 500.
```