```
      <link rel="icon" href="/icon.svg" type="image/svg+xml">
      <link rel="apple-touch-icon" href="/icon.png">

      <%# Includes all stylesheet files in app/assets/stylesheets %>
      <%= stylesheet_link_tag :app, "data-turbo-track": "reload" %>
      <%= javascript_importmap_tags %>
    </head>

    <body>
      <header class="bg-green-700">
        <%= image_tag 'logo.svg', alt: 'The Pragmatic Bookshelf' %>
        <h1><%= @page_title %></h1>
      </header>

      <section class="flex">
        <nav class="bg-green-900 p-6">
          <ul class="text-gray-300 leading-8">
            <li><a href="/">Home</a></li>
            <li><a href="/questions">Questions</a></li>
            <li><a href="/news">News</a></li>
            <li><a href="/contact">Contact</a></li>
          </ul>
        </nav>

        <main class="container mx-auto mt-4 px-5 flex">
          <%= yield %>
        </main>
      </section>
    </body>
  </html>
```

Apart from the usual HTML gubbins, this layout has a number of Rails-specific items. The Rails `stylesheet_link_tag` helper method generates a `<link>` tag to both Tailwind and our application's style sheets and specifies an option to enable Turbo,[48] which transparently works behind the scenes to speed up page changes within an application.

Finally, the `csrf_meta_tags` and `csp_meta_tag` methods set up all the behind-the-scenes data needed to prevent cross-site request forgery attacks, which will be important once we add forms in Chapter 12, *Task G: Check Out!*.