We make two small changes to the `_cart` template to use this new information:

rails80/depot_g/app/views/carts/_cart.html.erb

```
<div id="<%= dom_id cart %>">
  <h2 class="font-bold text-lg mb-3">Your Pragmatic Cart</h2>

»   <ul class="list-none list-inside">
      <% cart.line_items.each do |item| %>
»       <li><%= item.quantity %> &times; <%= item.product.title %></li>
      <% end %>
    </ul>
</div>
```

In addition to displaying the quantity for each line item, we remove the bullets that precede each item in the unordered list by changing `list-disc` to `list-none`. This shows one of many benefits to using a CSS framework to make our work more agile. When we make this change, we know not only that this change applies to this particular view; we also know that this change does *not* affect any other view—assurances we don't always have when authoring CSS style sheets.

Now that all the pieces are in place, we can go back to the store page and click the Add to Cart button for a product that's already in the cart. What we're likely to see is a mixture of individual products listed separately and a single product listed with a quantity of two. This is because we added a quantity of one to existing columns instead of collapsing multiple rows when possible. What we need to do next is migrate the data.

We start by creating a migration:

```
depot> bin/rails generate migration combine_items_in_cart
```

This time, Rails can't infer what we're trying to do, so we can't rely on the generated `change` method. What we need to do instead is to replace this method with separate `up` and `down` methods. First, here's the `up` method: