Iteration F1: Moving the Cart

Currently, our cart is rendered by the `show` action in the `CartController` and the corresponding `html.erb` template. We'd like to move that rendering into the sidebar. This means it'll no longer be in its own page. Instead, we'll render it in the layout that displays the overall catalog. You can do that using *partial templates*.

Partial Templates

Programming languages let you define *methods*. A method is a chunk of code with a name: invoke the method by the name, and the corresponding chunk of code gets run. And, of course, you can pass parameters to a method, which lets you write a piece of code that can be used in many different circumstances.

Think of Rails partial templates (*partials* for short) like a method for views. A partial is simply a chunk of a view in its own separate file. You can invoke (aka *render*) a partial from another template or from a controller, and the partial will render itself and return the results of that rendering. As with methods, you can pass parameters to a partial, so the same partial can render different results.

We'll use partials twice in this iteration. First let's look at the cart display:

rails80/depot_i/app/views/carts/_cart.html.erb

```
  <div id="<%= dom_id cart %>">
»   <h2 class="font-bold text-lg mb-3">Your Cart</h2>
»
»   <table class="table-auto">
»     <% cart.line_items.each do |line_item| %>
»       <tr>
»         <td class="text-right"><%= line_item.quantity %></td>
»         <td>&times;</td>
»         <td class="pr-2">
```