```
»           <%= line_item.product.title %>
»         </td>
»         <td class="text-right font-bold">
»           <%= number_to_currency(line_item.total_price) %>
»         </td>
»       </tr>
»     <% end %>
»
»     <tfoot>
»       <tr>
»         <th class="text-right pr-2 pt-2" colspan="3">Total:</th>
»         <td class="text-right pt-2 font-bold border-t-2 border-black">
»           <%= number_to_currency(cart.total_price) %>
»         </td>
»       </tr>
»     </tfoot>
»   </table>

    <%= button_to 'Empty Cart', cart, method: :delete,
      class: 'ml-4 rounded-lg py-1 px-2 text-white bg-green-600' %>
  </div>
```

It creates a list of table rows, one for each item in the cart. Whenever you find yourself iterating like this, stop and ask yourself, is this too much logic in a template? It turns out we can abstract away the loop by using partials. To do this, make use of the fact that you can pass a collection to the method that renders partial templates, and that method will automatically invoke the partial once for each item in the collection. Let’s rewrite our cart view to use this feature:

rails80/depot_j/app/views/carts/_cart.html.erb

```
  <div id="<%= dom_id cart %>">
    <h2 class="font-bold text-lg mb-3">Your Cart</h2>

    <table class="table-auto">
»     <%= render cart.line_items %>

      <tfoot>
        <tr>
          <th class="text-right pr-2 pt-2" colspan="3">Total:</th>
```