So, `@cart` is apparently `nil` when we display an index of our products. That makes sense, because it's set only in the store controller. We can even verify this using the web console provided at the bottom of the web page. Now that we know what the problem is, the fix is to avoid displaying the cart at all unless the value is set:

rails80/depot_l/app/views/layouts/application.html.erb

```
          <nav class="bg-green-900 p-6">
»           <% if @cart and not @cart.line_items.empty? %>
              <div id="cart" class="bg-white rounded p-2">
                <%= render @cart %>
              </div>
»           <% end %>

            <ul class="text-gray-300 leading-8">
              <li><a href="/">Home</a></li>
              <li><a href="/questions">Questions</a></li>
              <li><a href="/news">News</a></li>
              <li><a href="/contact">Contact</a></li>
            </ul>
          </nav>
```

With this change in place, our tests now pass once again. Imagine what could have happened. A change in one part of an application made to support a new requirement breaks a function implemented in another part of the application. If you're not careful, this can happen in a small application like Depot. Even if you're careful, this will happen in a large application.

Keeping tests up-to-date is an important part of maintaining your application. Rails makes this as easy as possible to do. Agile programmers make testing an integral part of their development efforts. Many even go so far as to write their tests first, before the first line of code is written.

So now we have a store with a cart in the sidebar. When we click to add an item to the cart, the page is redisplayed with an updated cart. But if our catalog is large, that redisplay might take a while. It uses bandwidth, and it uses server resources. Fortunately, we can use Turbo to make this better.