Now let's create the partial that this code references. Starting with code we extract from app/views/layouts/application.html.erb, add an HTML id attribute so that Turbo can identify the portion of the display that needs to be replaced. As we do this, we take care to ensure that the id is present even when the cart isn't displayed, which we do by adding an else clause:

rails80/depot_m/app/views/layouts/_cart.html.erb

```
<% if cart and not cart.line_items.empty? %>
  <div id="cart" class="bg-white rounded p-2">
    <%= render cart %>
  </div>
<% else %>
  <div id="cart"></div>
<% end %>
```

Finally, we update the template that we extracted this from to make use of the new partial:

rails80/depot_m/app/views/layouts/application.html.erb

```
<!DOCTYPE html>
<html>
  <head>
  <title><%= content_for(:title) || "Pragprog Books Online Store" %></title>
    <meta name="viewport" content="width=device-width,initial-scale=1">
    <meta name="apple-mobile-web-app-capable" content="yes">
    <meta name="mobile-web-app-capable" content="yes">
    <%= csrf_meta_tags %>
    <%= csp_meta_tag %>

    <%= yield :head %>

    <%# Enable PWA manifest for installable apps (make sure to enable in
        config/routes.rb too!) %>
    <%#= tag.link rel: "manifest", href: pwa_manifest_path(format: :json) %>

    <link rel="icon" href="/icon.png" type="image/png">
    <link rel="icon" href="/icon.svg" type="image/svg+xml">
    <link rel="apple-touch-icon" href="/icon.png">
```