In this file, we've updated the `h1` and removed the link back to the orders index. This template makes use of a partial named `_form`. We take a peek at that file and see many long lines repeating the same class definitions.

```
<div class="my-5">
   <%= form.label :name %>
   <%= form.text_field :name, class: [
     "block shadow-sm rounded-md border outline-hidden px-3 py-2 mt-2 w-full
",
     { "border-gray-400 focus:outline-blue-600": order.errors[:name].none?,
       "border-red-400 focus:outline-red-600": order.errors[:name].any? } ]
%>
</div>
```

That's quite a mouthful. The `class` attribute is an array. The first element of the array is a list of class names. The second element of the array is a hash of class names and conditions. If the condition is true, the class names are added to the list of classes. If the condition is false, the class names aren't added. The net result is a gray border if there are no errors and a red border if there are errors. An outline is also defined, but hidden, which appears to be an oversight.[63]

Let's introduce a pair of CSS rules so that we can clean this up:

rails80/depot_o/app/assets/tailwind/application.css

```
   @import "tailwindcss";

» .input-field {
»   @apply
»   block shadow-sm rounded-md border px-3 py-2 mt-2 w-full
»   border-gray-400 focus:outline-blue-600
» }
»
» .field_with_errors .input-field {
»   @apply
»   border-red-400 focus:outline-red-600
» }
```

There is a lot to unpack in this short little file: