```
      click_on "Checkout"

      assert has_no_field? "Routing number"
      assert has_no_field? "Account number"
      assert has_no_field? "Credit card number"
      assert has_no_field? "Expiration date"
      assert has_no_field? "Po number"

      select "Check", from: "Pay type"

      assert has_field? "Routing number"
      assert has_field? "Account number"
      assert has_no_field? "Credit card number"
      assert has_no_field? "Expiration date"
      assert has_no_field? "Po number"

      select "Credit card", from: "Pay type"

      assert has_no_field? "Routing number"
      assert has_no_field? "Account number"
      assert has_field? "Credit card number"
      assert has_field? "Expiration date"
      assert has_no_field? "Po number"

      select "Purchase order", from: "Pay type"

      assert has_no_field? "Routing number"
      assert has_no_field? "Account number"
      assert has_no_field? "Credit card number"
      assert has_no_field? "Expiration date"
      assert has_field? "Po number"
    end
  end
```

As you can see, it's largely a repetition of a few lines of code with minor variations, prefaced by a few discrete steps: `visit` a URL, find the `:first` button with the text `"Add to Cart"` and `click_on` it. Then `click_on` the button labeled `"Checkout"`. We then `select` various pay types and verify what fields we expect to see and what fields we expect *not* to see.