controller. We need to provide this information by editing our `config/routes.rb` file:

rails80/depot_r/config/routes.rb

```
    Rails.application.routes.draw do
»     get "admin" => "admin#index"
      resources :users
      resource :session
      resources :passwords, param: :token
      resources :orders
      resources :line_items
      resources :carts
      root "store#index", as: "store_index"
      resources :products
      # Define your application routes per the DSL in
      # https://guides.rubyonrails.org/routing.html

      # Reveal health status on /up that returns 200 if the app boots with no
      # exceptions, otherwise 500.
      # Can be used by load balancers and uptime monitors to verify that the
      # app is live.
      get "up" => "rails/health#show", as: :rails_health_check

      # Render dynamic PWA files from app/views/pwa/*
      # (remember to link manifest in application.html.erb)
      # get "manifest" => "rails/pwa#manifest", as: :pwa_manifest
      # get "service-worker" => "rails/pwa#service_worker", as:
    :pwa_service_worker

      # Defines the root path route ("/")
      # root "posts#index"
    end
```

We've touched this before, when we added a `root` statement in*Iteration C1: Creating the Catalog Listing*. What the `generate` command adds to this file are fairly generic `get` statements for each action specified.

Now we change where logged-in users are redirected to after logging in:

rails80/depot_r/app/controllers/concerns/authentication.rb