to change the code to *not* do that so that you can properly test the login functionality.

When the system is freshly installed on a new machine, no administrators are defined in the database, and hence no administrator can log on. But if no administrator can log on, then no one can create an administrative user.

Change the code so that if no administrator is defined in the database, any username works to log on (allowing you to quickly create a real administrator).

- Experiment with `rails console`. Try creating products, orders, and line items. Watch for the return value when you save a model object—when validation fails, you'll see `false` returned. Find out why by examining the errors:

```
>> prd = Product.new
=> #<Product id: nil, title: nil, description: nil, image_url:
nil, created_at: nil, updated_at: nil, price:
#<BigDecimal:246aa1c,'0.0',4(8)>>
>> prd.save
=> false
>> prd.errors.full_messages
=> ["Image url must be a URL for a GIF, JPG, or PNG image",
    "Image url can't be blank", "Price should be at least 0.01",
    "Title can't be blank", "Description can't be blank"]
```

- We've gotten our tests working by performing a login, but we haven't yet written tests that verify that access to sensitive data requires login. Write at least one test that verifies this by calling `logout` and then attempting to fetch or update some data that requires authentication.

Footnotes

[79] https://api.rubyonrails.org/classes/ActionController/HttpAuthentication/Digest.html

[80] https://github.com/rails/rails/blob/5-1-stable/activemodel/lib/active_model/secure_password.rb