controller and action, but we'll want this to cause the locale to be set differently.

At this point, we've made a lot of changes to `config.routes`, and with the nesting and all the optional parts to the path, the gestalt might be hard to visualize. Never fear—when running a server in development mode, Rails provides a visual aid. All you need to do is navigate to http://localhost:3000/rails/info/routes, and you'll see a list of all your routes. You can even filter the list, as shown in the screenshot shown, to quickly find the route you're interested in. More information on the fields shown in this table can be found in the description of rake routes.

Routes

Routes match in priority from top to bottom

Search

Helper (Path / Url)	HTTP Verb	Path	Controller#Action	Source Location
		/assets	Propshaft::Server	propshaft (1.1.0) lib/propshaft/railtie.rb:47
admin_path	GET	/admin(.:format)	admin#index	/Users/rubys/git/awdwr8/work/config/routes.rb:2
rails_health_check_path	GET	/up(.:format)	rails/health#show	/Users/rubys/git/awdwr8/work/config/routes.rb:3
users_path	GET	/users(.:format)	users#index	/Users/rubys/git/awdwr8/work/config/routes.rb:5
	POST	/users(.:format)	users#create	/Users/rubys/git/awdwr8/work/config/routes.rb:5
new_user_path	GET	/users/new(.:format)	users#new	/Users/rubys/git/awdwr8/work/config/routes.rb:5
edit_user_path	GET	/users/:id/edit(.:format)	users#edit	/Users/rubys/git/awdwr8/work/config/routes.rb:5

With the routing in place, we're ready to extract the locale from the parameters and make it available to the application. To do this, we need to