Iteration J2: Translating the Storefront

Now it's time to begin providing the translated text. Let's start with the layout since it's pretty visible. We replace any text that needs to be translated with calls to `I18n.translate`. Not only is this method conveniently aliased as `I18n.t`, but a helper named `t` is provided.

The parameter to the translate function is a unique dot-qualified name. We can choose any name we like, but if we use the `t` helper function provided, names that start with a dot will first be expanded using the name of the template.

So, let's do that:

rails80/depot_t/app/views/layouts/application.html.erb

```
<!DOCTYPE html>
<html>
  <head>
  <title><%= content_for(:title) || "Pragprog Books Online Store" %></title>
    <meta name="viewport" content="width=device-width,initial-scale=1">
    <meta name="apple-mobile-web-app-capable" content="yes">
    <meta name="mobile-web-app-capable" content="yes">
    <%= csrf_meta_tags %>
    <%= csp_meta_tag %>

    <%= yield :head %>

    <%# Enable PWA manifest for installable apps (make sure to enable in
        config/routes.rb too!) %>
    <%#= tag.link rel: "manifest", href: pwa_manifest_path(format: :json) %>

    <link rel="icon" href="/icon.png" type="image/png">
    <link rel="icon" href="/icon.svg" type="image/svg+xml">
    <link rel="apple-touch-icon" href="/icon.png">

    <%# Includes all stylesheet files in app/assets/stylesheets %>
    <%= stylesheet_link_tag :app, "data-turbo-track": "reload" %>
```